



WINDOW FILM PERFORMANCE SPECIFICATIONS

	Transmission % Visible Light	% Total Solar Energy Rejection	% IR Energy Rejection	% Visible Light Reflection	Protection % Ultraviolet	% Glare Reduction***
CARBON CLASSIC SERIES		Budget -friendly enhanced style				
Classic 05	3.4	45	11.9	9	>99	93
Classic 20	14.8	37	10.3	8	>99	79
Classic 35	30	35	11	8	>99	60
Classic 50	49.9	28	10.3	8	>99	51

	Transmission % Visible Light	% Total Solar Energy Rejection	% IR Energy Rejection	% Visible Light Reflection	Protection % Ultraviolet	% Glare Reduction***
CARBON PLUS SERIES		Good heat rejection and enhanced style				
Plus 03	1	46	11.6	6	>99	94
Plus 05	4.1	45	10.9	6	>99	93
Plus 15	9.8	44	9.7	6	>99	93
Plus 20	20.6	38	10.4	6	>99	79
Plus 35	35.2	35	10	6	>99	60
Plus 50	51.9	27	10	6	>99	50

	Transmission % Visible Light	% Total Solar Energy Rejection	% IR Energy Rejection	% Visible Light Reflection	Protection % Ultraviolet	% Glare Reduction***
CERAMIC CLASSIC IR30 SERIES		Excellent heat rejection and enhanced style				
Classic IR30 03	3.5	50.5	33.1	5	>99	97
Classic IR30 05	5.3	50	31.7	5.1	>99	94
Classic IR30 15	9.9	48.6	34.4	5.1	>99	88
Classic IR30 20	20	45.5	34.2	5	>99	77
Classic IR30 35	35.3	41.2	31.9	5.3	>99	65
Classic IR30 50	43.1	35.5	31	6.1	>99	47
Classic IR30 70	72	27.2	30.1	6.3	>99	44

	Transmission % Visible Light	% Total Solar Energy Rejection	% IR Energy Rejection	% Visible Light Reflection	Protection % Ultraviolet	% Glare Reduction***
CERAMIC PLUS IR55 SERIES		Most advanced ceramic technology for our maximum heat rejection				
Plus IR55 05	2.3	34.3	59	4.8	>99	96.2
Plus IR55 20	19.9	46	57	5.9	>99	79.2
Plus IR55 35	33.1	44	53	5.6	>99	71.6
Plus IR55 50	42.2	39	56.6	5.9	>99	48.8